

### Feature:

- Flexible, Free to crimp
- Can be cut and connected to extend
- Low input voltage, safe
- High efficiency and stability, no shadows at the junction
- Adhesive backing for an easy peel-and-stick installation



### Application

- ◆ Mall lighting, Home lighting, Indoor project and etc.


### Product Specification

	Model.	L12A130CT0BJDA7	L22A130CT0BJDA0
Basic Data	Input Voltage	DC 12V	DC 24V
	Power (W)	13 + 13	
	Lumen (lm) (4000°K)	1235	
	Efficiency (lm/W)	100	
	CCT (°K)	2700 - 6500	
	CRI	R90	
	Beam Angle(°)	120	
	Protection Grade (Technology)	IP 20	
	Life Time (hrs)	L70B50:36000H	
	LED Quantity (pcs)	120 + 120	
	Working Temperature	-10°C~40°C	
	Working Humidity	30%~65%RH	
	Maximum Connecting Length	5 mt	
	Appearance Information	Product Size(mm)	L5000 x W5 x H1,4 mm
Material		/	
Color		Two sided white FPC	
Packing Information	Carton Size(mm)	420 x 275 x 310 mm	
	Quantity/CTN(pcs)	50	
	Quantity/Container(pcs)	20GP: 34000 40HQ: 80000	

**Product Size(mm):**

**L12A130DT0BJDA0**

12VDC



**L22A130DT0BJDA0**

24VDC 8.33mm



**Notes:**

- ◆ Specifications above are typical values. There is deviation between measured parameters and typical values. The light distribution curve and light illuminance are the test data of neutral white samples and for reference only.