

Feature:

- Flexible, Free to crimp
- Can be cut and connected to extend
- Low input voltage, safe
- High efficiency and stability, no shadows at the junction
- Adhesive backing for an easy peel-and-stick installation



RoHS
COMPLIANT

Application


- ◆ Mall lighting, Home lighting, Indoor project and etc.

Product Specification

Basic Data	Model.	L22B169D30CEIA0
	Input Voltage	DC 24V
	Power (W)	16,9
	Lumen (lm)	1859
	Efficiency (lm/W)	110
	CCT (°K)	3000
	CRI	R95
	Beam Angle(°)	120
	Protection Grade (Technology)	IP 20
	Life Time (hrs)	L70B50:36000H
	LED Quantity (pcs)	160
	Working Temperature	-10°C~40°C
	Working Humidity	30%~65%RH
Appearance Information	Maximum Connecting Length	5 mt
	Product Size(mm)	L5000 x W8 x H1,4 mm
	Material	/
Packing Information	Color	Two sided white FPC
	Carton Size(mm)	420 x 275 x 310 mm
	Quantity/CTN(pcs)	40
	Quantity/Container(pcs)	20GP: 27000 40HQ: 64000

Product Size(mm):

L22B169D30BFIA0



Notes:

- ◆ Specifications above are typical values. There is deviation between measured parameters and typical values. The light distribution curve and light illuminance are the test data of neutral white samples and for reference only.