

Feature:

- Flexible, Free to crimp
- Can be cut and connected to extend
- Low input voltage, safe
- High efficiency and stability, no shadows at the junction
- Adhesive backing for an easy peel-and-stick installation



Application


- ◆ Mall lighting, Home lighting, Indoor project and etc.

Product Specification


	Model.	L22C078DXXBBYA1	L22C117DXXBKYA3	L22C169DXXBEYA0
Basic Data	Input Voltage	DC 24V		
	Power (W)	7,8	11,7	16,9
	Lumen (lm)	27-30 1053 / 40 1170	27-30 1580 / 40 1755	27-30 2282 / 40 2535
	Efficiency (lm/W)	Y = Q 135 / T 150		
	CCT (°K)	XX = 27 2700 / 30 3000 / 40 4000		
	CRI	R90		
	Beam Angle(°)	120		
	Protection Grade (Technology)	IP 20		
	Life Time (hrs)	L70B50:36000H		
	LED Quantity (pcs)	80	112	160
	Working Temperature	-10°C~40°C		
	Working Humidity	30%~65%RH		
	Maximum Connecting Length	5 mt		
	Appearance Information	Product Size(mm)	L5000 x W10 x H1,4 mm	
Material		/		
Color		Two sided white FPC		
Packing Information	Carton Size(mm)	420 x 275 x 310 mm		
	Quantity/CTN(pcs)	50		40
	Quantity/Container(pcs)	20GP: 34000	40HQ: 80000	20GP: 27000 40HQ: 64000

Product Size(mm):


L22C078DXXBBYA1:



L22C117DXXBKYA3:



L22C169DXXBFYA0:



Notes:

- ◆ Specifications above are typical values. There is deviation between measured parameters and typical values. The light distribution curve and light illuminance are the test data of neutral white samples and for reference only.